

Material Safety Data Sheet



Marble & stone penetrating sealer

Section 1. Chemical product and company identification

Manufacturer: HG International b.v.Code: 1211064Address: Damsluisweg 70 1332 EJ AlmereMSDS#: 2.03

Country: Netherlands: Netherlands: Netherlands: 5/19/2010.

Telephone No.: : +31 (0)36 54 94 700 Print date : 5/19/2010. : +31 (0)36 54 94 744 : P. Stienstra **Fax** Responsible name : +1.705.726.5445 **Internet:** : www.hg.eu **Telephone No.:** Fax : +1.705.734.0857 : Solstrand Trading **Supplier**

Address : 60 Lockhart road Barrie, Ontario L4N 9G8 Country : Canada

Material uses : Protects against pollutant and stains.

In Case of Emergency

gency : Chem. Tel Inc. (813) 248 0585 or Toll free (800) 255 3924

Section 2. Composition, Information on Ingredients

Name	CAS#	% by weight	Exposure limits	
Naphtha (petroleum), hydrodesulfurized heavy	64742-82-1	30 - 100	Not available.	
isobutyl methacrylate, 2-ethylhexyl acrylate polymer	27881-32-9	5-15	Not available.	
Naphta (petroleum) low boiling naphta unspecified	64742-95-6	0-1	Not available.	
1,2,4-Trimethylbenzene	95-63-6	0 - 1	Not available.	
Mesitylene	108-67-8	0-0.1	Not available.	
cumene	98-82-8	0-0.05	Not available.	
Xylene	1330-20-7	0-0.01	Not available.	

Section 3. Hazards identification

Physical State and

Appearance

: Liquid.

Emergency overview

: WARNING!

FLAMMABLE LIQUID AND VAPOR. COMBUSTIBLE.

Flammable liquid. Keep away from heat, sparks and flame. Avoid breathing vapor or mist. Avoid contact with skin and clothing. Use only with adequate ventilation. Keep container tightly closed and sealed until

ready for use.

Routes of entry

: Dermal contact. Eye contact. Inhalation. Ingestion.

Potential acute health effects

Eyes: Inflammation of the eye is characterized by redness, watering and itching.

Skin: Harmful if absorbed through the skin.

Inhalation: Harmful by inhalation.

Ingestion: Aspiration hazard if swallowed. Can enter lungs and cause damage.

Potential chronic health

effects

: CARCINOGENIC EFFECTS: Not available. MUTAGENIC EFFECTS: Not available. TERATOGENIC EFFECTS: Not available.

Medical conditions aggravated by overexposure:

: None known.

Over-exposure signs/symptoms

: Not available.

See toxicological Information (section 11)

Section 4. First aid measures

Eye Contact

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.

Skin Contact

: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Inhalation

Move exposed person to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Ingestion

: Wash out mouth with water. Remove dentures if any. Move exposed person to fresh air. Keep person warm and at rest. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Notes to Physician

Not available.

Section 5. Fire fighting measures

Flammability of the product : May be combustible at high temperature.

Auto-ignition Temperature

: 210°C (410°F)

Flash Points

: Closed cup: 40°C (104°F) [Pensky-Martens.]

Flammable limits

: Not available.

Products of combustion

: Decomposition products may include the following materials:

carbon oxides

Fire hazards in presence of

various substances

: Flammable.

: Not available.

Explosion hazards in

presence of various

substances

Fire fighting media and

instructions

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Flammable liquid. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard.

Special protective equipment

for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Special remarks on fire hazards

: COMBUSTIBLE.

Special remarks on explosion: No additional remark.

hazards

Section 6. Accidental release measures

Personal precautions

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see section 8).

Marble & stone penetrating sealer

Environmental precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Page: 3/7

Methods for cleaning up

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.

Section 7. Handling and storage

Handling

: Keep container closed. Use only with adequate ventilation. Keep away from heat, sparks and flame. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Do not ingest.

Storage

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure Controls, Personal Protection

Engineering controls

Personal protection

Eyes: Recommended: safety glasses with side shields Skin: Recommended: Work uniform or laboratory coat.

Respiratory: Recommended: Ventilation is normally required when handling or using this product. Wear appropriate

respirator when ventilation is inadequate.

Hands: >8 hours (breakthrough time): polyvinyl alcohol (PVA)

Other protection: Not available.

Personal protective equipment (Pictograms)



Personal protection in case of a large spill

: Splash goggles. Full suit. Boots. Gloves. Suggested protective clothing might not be adequate. Consult a specialist before handling this product.

Product Name

Naphtha (petroleum), hydrodesulfurized heavy isobutyl methacrylate, 2-ethylhexyl acrylate polymer 1,2,4-Trimethylbenzene

Xylene Naphta (petroleum) low boiling naphta unspecified Mesitylene

cumene Consult local authorities for acceptable exposure limits. **Exposure limits**

Not available. Not available. Not available.

Not available. Not available.

Not available. Not available.

Section 9. Physical and chemical properties

Physical State and

Appearance

: Liquid.

Color Colorless. Odor : Characteristic. Not available. pН

: 0,806 g/cm3 [20°C (68°F)] Relative density

Viscosity : Not available.

Solubility Partially soluble in the following materials: diethyl ether.

Insoluble in the following materials: cold water and hot water.

Closed cup: 40°C (104°F) [Pensky-Martens.] Flash point

Flammability (solid, gas) Not applicable. : Not available. **Explosive properties Oxidizing properties** : Not available.

Physical chemical comments: Soluble in the following materials: Other Solvents. Soluble

Section 10. Stability and reactivity

Stability and Reactivity : The product is stable.

Conditions of instability : Keep away from heat, sparks and flame. Stable under recommended storage and handling conditions

(see section 7).

substances

Incompatibility with various: Not considered to be reactive according to our database.

Hazardous Decomposition

Products

: Under normal conditions of storage and use, hazardous decomposition products should not be

produced.

: Will not occur. **Hazardous polymerization**

Section 11. Toxicological information

Naphtha (petroleum),	LD50	>5000 mg/kg	Oral	Rat
hydrodesulfurized heavy	LD50	>3000 mg/kg	Dermal	Rabbit
Xylene	LD50	4300 mg/kg	Oral	Rat
	LD50	2119 mg/kg	Oral	Mouse
	LD50	4300 mg/kg	Oral	Mammal
	LD50	>1700 mg/kg	Dermal	Rabbit
	LD50	1700 mg/kg	Dermal	Rabbit
	LDLo	50 mg/kg	Oral	human
Naphta (petroleum) low boiling	LD50	8400 mg/kg	Oral	Rat
naphta unspecified	LD50	>2150 mg/kg	Oral	quail
cumene	LD50	1400 mg/kg	Oral	Rat
	LD50	12750 mg/kg	Oral	Mouse

Chronic effects on humans

: May be harmful if swallowed.

Other toxic effects on humans

Extremely hazardous by the following route of exposure: of eye contact (irritant), of inhalation (lung

irritant).

Special remarks on toxicity

to animals

: Not available.

Special remarks on chronic effects on humans

: Not available.

Special remarks on other toxic effects on humans

: Not available.

Specific effects

: No known significant effects or critical hazards. Carcinogenic effects : No known significant effects or critical hazards. Mutagenic effects : No known significant effects or critical hazards. Reproduction toxicity

Section 12. Ecological information

Naphtha (petroleum), hydrodesulfurized heavy 1,2,4-Trimethylbenzene	Trout (LC50) Shrimp. (IC50) Pimephales promelas (LC50)	96 hour(s) 96 hour(s) 96 hour(s)	41.4 mg/l 4.3 mg/l 7.72 mg/l
isobutyl methacrylate, 2-ethylhexyl acrylate polymer		Not available.	Not available.
Xylene	Oncorhynchus mykiss (LC50) Oncorhynchus mykiss (LC50) Lepomis macrochirus (LC50) Lepomis macrochirus (LC50) Lepomis macrochirus (LC50) Pimephales promelas (LC50)	96 hour(s) 96 hour(s) 96 hour(s) 96 hour(s) 96 hour(s) 96 hour(s)	3.3 mg/l 8.2 mg/l 8.6 mg/l 12 mg/l 13.3 mg/l 13.4 mg/l
Naphta (petroleum) low boiling naphta unspecified	Not available.	Not available.	Not available.
Mesitylene	Scenedesmus subspicatus (EC50)	48 hour(s)	25 mg/l
	Scenedesmus subspicatus (EC50)	48 hour(s)	53 mg/l
cumene	Daphnia magna (EC50) Daphnia magna (EC50) Oncorhynchus mykiss (LC50) Poecilia reticulata (LC50) Pimephales promelas (LC50)	48 hour(s) 48 hour(s) 96 hour(s) 96 hour(s) 96 hour(s)	10.6 mg/l 11.2 mg/l 2.7 mg/l 5.1 mg/l 6.32 mg/l

BOD and COD : Not available.

Biodegradable/OECD : Not available.

Mobility : Not determined.

Products of degradation

Toxicity of the products of

biodegradation

Special remarks on the products of biodegradation

: Products of degradation: carbon oxides (CO, CO₂) and water.

: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

: Not available.

Section 13. Disposal considerations

Waste information

The generation of waste should be avoided or minimized wherever possible. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Waste stream : Not available.

Consult your local or regional authorities.

Section 14. Transport information

Regulatory Information	UN number	Proper shipping name	Class	Packing group	Label	Additional information
DOT Classification	3295	UN 3295, HYDROCARBONS, LIQUID, N.O.S., (White Spirit, 86%, mixture), Class 3, PG III, (FP 104°F) (Naphtha (petroleum), hydrodesulfurized heavy). Marine pollutant	Combustible liquid.	III		Marine pollutant Marine pollutant (P) Limited quantity Yes. Special provisions Limited Quantity Remarks ORM-D / CONSUMER COMMODITY

Marble & st	tone pen	etrating sealer			Page: 6/7
TDG Classification	3295	UN 3295, HYDROCARBONS, LIQUID, N.O.S., (White Spirit, 86%, mixture), Class 3, PG III, (FP 104°F) (Naphtha (petroleum), hydrodesulfurized heavy). Marine pollutant	3	III	Marine pollutant Marine pollutant (P) Special provisions ORM-D / CONSUMER COMMODITY Remarks Limited Quantity
ADR/RID Class	3295	UN 3295, "dangerous goods in limited quantities of class 3", III, ADR (Naphtha (petroleum), hydrodesulfurized heavy)	3	III	Hazard identification number 30 Reportable quantity 45 Limited quantity LQ7 Remarks Limited quantity for upto 5 litre inner packing Else; UN 3295, HYDROCARBONS, LIQUID N.O.S., (White Spirit, mixture) class 3, III, ADR Keep in frostfree area
IMDG Class	3295	"dangerous goods in limited quantities of class 3" UN 3295, PG III (Naphtha (petroleum), hydrodesulfurized heavy). Marine pollutant (Naphtha (petroleum), hydrodesulfurized heavy, Naphta (petroleum) low boiling naphta unspecified)	3	III	Emergency schedules (EmS) F-E, S-E Marine pollutant Marine pollutant (P) Reportable quantity 30 Remarks Limited quantity for upto 5 litre inner packing Else; HYDROCARBONS, LIQUID N.O.S., (White Spirit, 85%, mixture) class 3, UN 3295, PG III Keep in frostfree area
IATA-DGR Class	3295	"dangerous goods in limited quantities of class 3" UN 3295, PG III (Naphtha (petroleum), hydrodesulfurized heavy)	3	III	Remarks Keep in frostfree area

Section 15. Regulatory information

WHMIS (Canada) : Class B-3: Combustible liquid with a flash point between 37.8°C (100°F) and 93.3°C (200°F).

CEPA Toxic substances: None of the components are listed.

Canadian ARET: None of the components are listed. **Canadian NPRI**: None of the components are listed.

Alberta Designated Substances: None of the components are listed. Ontario Designated Substances: None of the components are listed. Quebec Designated Substances: None of the components are listed.

International regulations

EINECS:

DSCL (EEC): R10- Flammable.

R65- Harmful: may cause lung damage if swallowed.

R66- Repeated exposure may cause skin dryness or cracking.

R67- Vapors may cause drowsiness and dizziness.

R51/53- Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

International lists: Australia inventory (AICS): Not determined.

China inventory (IECSC): Not determined.
Korea inventory (KECI): Not determined.
Philippines inventory (PICCS): Not determined.
Japan inventory (ENCS): Not determined.

Section 16. Other information

Label Requirements : FLAMMABLE LIQUID AND VAPOR. COMBUSTIBLE.

Hazardous Material Information System (U.S.A.)



National Fire Protection Association (U.S.A.)



References : Not available.

Other special considerations : Not available.

Date of printing : 5/19/2010.

Date of issue : 5/19/2010.

Date of previous issue : No previous validation.

Version : 2.03

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.