SAFETY DATA SHEET

HG furniture wax remover



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : HG furniture wax remover

Product code : 270 030 ART

Product description: Consumer product.

Product type : Liquid.

Other means of : Not available.

identification

1.2 Relevant identified uses of the substance or mixture and uses advised against

Removes the top layer of old wax layers thus removing stains and dirt.

1.3 Details of the supplier of the safety data sheet

HG International BV

Damsluisweg 70 - NL-1332 EJ - Almere - The Netherlands Tel.: +31 (0)36 54 94 700 - Fax: +31 (0)36 54 94 744

Email: info@hg.eu - Internet: www.hg.eu

e-mail address of person : safety@hg.eu

responsible for this SDS

National contact

HG Hagesan UK Ltd.

Unit 2

Lanswood Park Broomfield Road Elmstead Market Colchester

Essex CO7 7FD

Tel.: 0044 (0)1206 822744 Fax: 0044 (0)1206 827019

1.4 Emergency telephone number

National advisory body/Poison Centre

Telephone number : England and Wales

NHS Direct: 0845 4647

Scotland

NHS 24: 08454 24 24 24

Republic of Ireland

01 809 2166

Supplier

Telephone number : +31 (0)36 54 94 777 **Hours of operation** : Mo-Fr 9.00-17.00

Information limitations : Only for medical personnel.

Date of issue/Date of revision : 25-7-2019 Date of previous issue : 19-12-2018 Version : 2.01 1/14

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 3, H226 **STOT SE 3, H336**

STOT RE 1, H372 (central nervous system (CNS))

Asp. Tox. 1, H304 Aquatic Chronic 2, H411

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

Ingredients of unknown

toxicity

Ingredients of unknown

ecotoxicity

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms









Signal word Danger

Hazard statements Flammable liquid and vapour.

May be fatal if swallowed and enters airways.

May cause drowsiness or dizziness.

Causes damage to organs through prolonged or repeated exposure. (central

nervous system (CNS))

Toxic to aquatic life with long lasting effects.

Precautionary statements

General : If medical advice is needed: Have product container or label at hand. Keep out of

reach of children.

Prevention : Avoid breathing vapour. Wash hands thoroughly after handling. Do not eat, drink or

smoke when using this product.

Response : IF SWALLOWED: Immediately call a POISON CENTER or physician. Do NOT

induce vomiting.

: Store in a well-ventilated place. Keep container tightly closed. **Storage**

: Dispose of contents and container in accordance with all local, regional, national **Disposal**

and international regulations.

Hazardous ingredients

Supplemental label

elements

: Naphtha (petroleum), hydrodesulfurized heavy

: Contains (R)-p-mentha-1,8-diene - Citronellal. May produce an allergic reaction.

Repeated exposure may cause skin dryness or cracking.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

: Not applicable.

Special packaging requirements

Containers to be fitted with child-resistant

fastenings

: Yes, applicable.

Tactile warning of danger: Yes, applicable.

Date of issue/Date of revision : 25-7-2019 Date of previous issue : 19-12-2018 Version

SECTION 2: Hazards identification

2.3 Other hazards

Other hazards which do not result in classification

: None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Regulation (EC) No. 1272/2008 [CLP]	Туре
Naphtha (petroleum), hydrodesulfurized heavy	EC: 265-185-4 CAS: 64742-82-1	≥90	Flam. Liq. 3, H226 STOT SE 3, H336 STOT RE 1, H372 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 EUH066	[1]
(R)-p-mentha-1,8-diene	EC: 227-813-5 CAS: 5989-27-5	<0,25	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1, H317 Asp. Tox. 1, H304 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	[1]
diphenyl ether	EC: 202-981-2 CAS: 101-84-8	<0,25	Eye Irrit. 2, H319 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 3, H412	[1] [2]
			See Section 16 for the full text of the H statements declared above.	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [5] Substance of equivalent concern
- [6] Additional disclosure due to company policy

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

Inhalation

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Date of issue/Date of revision : 25-7-2019 Date of previous issue : 19-12-2018 Version : 2.01 3/14

HG furniture wax remover

SECTION 4: First aid measures

Skin contact

Wash skin thoroughly with soap and water or use recognised skin cleanser.
Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes.
Get medical attention following exposure or if feeling unwell. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

: Get medical attention immediately. Call a poison center or physician. Remove dentures if any. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

Eye contact : No specific data.

Inhalation : Adverse symptoms may include the following:

nausea or vomiting

headache

drowsiness/fatigue dizziness/vertigo unconsciousness

Skin contact: Adverse symptoms may include the following:

irritation dryness cracking

Ingestion : Adverse symptoms may include the following:

nausea or vomiting

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

Specific treatments: No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

: Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing

media

: Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture

: Flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous combustion products

: Decomposition products may include the following materials:

carbon dioxide carbon monoxide

5.3 Advice for firefighters

Date of issue/Date of revision: 25-7-2019Date of previous issue: 19-12-2018Version: 2.014/14

SECTION 5: Firefighting measures

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

6.3 Methods and material for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with noncombustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

6.4 Reference to other sections

: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Do not breathe vapour or mist. Do not swallow. Avoid contact with eyes, skin and clothing. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment.

Date of issue/Date of revision : 25-7-2019 Date of previous issue : 19-12-2018 Version : 2.01

HG furniture wax remover

SECTION 7: Handling and storage

Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Seveso Directive - Reporting thresholds (in tonnes)

Danger criteria

	Notification and MAPP threshold	Safety report threshold
P5c	5000	50000
E2	200	500

7.3 Specific end use(s)

Recommendations

Industrial sector specific : Not available.

solutions

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
diphenyl ether	EH40/2005 WELs (United Kingdom (UK), 12/2011). TWA: 7,1 mg/m³ 8 hours. Form: Vapour TWA: 1 ppm 8 hours. Form: Vapour

procedures

Recommended monitoring: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

No DNELs/DMELs available.

PNECs

Date of issue/Date of revision : 25-7-2019 Date of previous issue : 19-12-2018 Version : 2.01

SECTION 8: Exposure controls/personal protection

No PNECs available

8.2 Exposure controls

Appropriate engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Skin protection

Hand protection

: Not applicable

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Thermal hazards

Environmental exposure

controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Liquid. Colour : Yellow. **Odour** : Solvent. **Odour threshold** Not available. pH : Not available. : -20°C

Melting point/freezing point

Initial boiling point and

boiling range

: 157 to 198°C

: Closed cup: 46°C Flash point Not available. **Evaporation rate**

Date of issue/Date of revision : 25-7-2019 Date of previous issue : 19-12-2018 Version : 2.01

HG furniture wax remover

SECTION 9: Physical and chemical properties

Flammability (solid, gas) : Not available. Upper/lower flammability or : Lower: 0,6% Upper: 6,5% explosive limits : Not available. Vapour pressure Not available. Vapour density

0.78 Relative density

: Partially soluble in the following materials: diethyl ether. Solubility(ies)

Insoluble in the following materials: cold water and hot water.

Partition coefficient: n-octanol/ : Not available.

water

: 210°C **Auto-ignition temperature**

Decomposition temperature : Not available.

Viscosity : Dynamic (room temperature): 1,28 mPa·s

Explosive properties : Not available. **Oxidising properties** Not available.

9.2 Other information

Solubility in water : Not available.

No additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld,

braze, solder, drill, grind or expose containers to heat or sources of ignition.

10.5 Incompatible materials : Reactive or incompatible with the following materials:

oxidizing materials

10.6 Hazardous

decomposition products

Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
(R)-p-mentha-1,8-diene	LD50 Dermal	Rabbit	>5 g/kg	-
	LD50 Oral	Rat	4400 mg/kg	-
diphenyl ether	LD50 Dermal	Rabbit	>7940 mg/kg	-
	LD50 Oral	Rat	2450 mg/kg	-

Conclusion/Summary : Not available.

Acute toxicity estimates

Not available.

Irritation/Corrosion

Date of issue/Date of revision : 25-7-2019 Date of previous issue : 19-12-2018 Version

HG furniture wax remover

SECTION 11: Toxicological information

Product/ingredient name	Result	Species	Score	Exposure	Observation
diphenyl ether	Skin - Mild irritant	Rabbit		24 hours 500 milligrams	-

Conclusion/Summary

: Not available.

Sensitisation

Conclusion/Summary

: Not available.

Mutagenicity

Conclusion/Summary

: Not available.

Carcinogenicity

Conclusion/Summary

: Not available.

Reproductive toxicity

Conclusion/Summary

: Not available.

Teratogenicity

Conclusion/Summary: Not available.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
HG furniture wax remover Naphtha (petroleum), hydrodesulfurized heavy			Narcotic effects Narcotic effects

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
HG furniture wax remover	Category 1	Not determined	central nervous system (CNS)
Naphtha (petroleum), hydrodesulfurized heavy	Category 1	Not determined	Not determined

Aspiration hazard

Product/ingredient name	Result
HG furniture wax remover	ASPIRATION HAZARD - Category 1
Naphtha (petroleum), hydrodesulfurized heavy	ASPIRATION HAZARD - Category 1
(R)-p-mentha-1,8-diene	ASPIRATION HAZARD - Category 1

Information on likely routes

of exposure

: Not available.

Potential acute health effects

Eye contact: No known significant effects or critical hazards.

Inhalation : Can cause central nervous system (CNS) depression. May cause drowsiness or

dizziness.

Skin contact: Defatting to the skin. May cause skin dryness and irritation.

Ingestion : Can cause central nervous system (CNS) depression. May be fatal if swallowed

and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.

Inhalation : Adverse symptoms may include the following:

nausea or vomiting

headache

drowsiness/fatigue dizziness/vertigo unconsciousness

Date of issue/Date of revision: 25-7-2019Date of previous issue: 19-12-2018Version: 2.019/14

HG furniture wax remover

SECTION 11: Toxicological information

Skin contact: Adverse symptoms may include the following:

irritation dryness cracking

Ingestion: Adverse symptoms may include the following:

nausea or vomiting

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate

: Not available.

effects

Potential delayed effects :

: Not available.

Long term exposure

Potential immediate

: Not available.

effects

Potential delayed effects: Not available.

Potential chronic health effects

Not available.

Conclusion/Summary: Not available.

General : Causes damage to organs through prolonged or repeated exposure. Prolonged or

repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Teratogenicity : No known significant effects or critical hazards.
 Developmental effects : No known significant effects or critical hazards.
 Fertility effects : No known significant effects or critical hazards.

Other information : Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
(R)-p-mentha-1,8-diene	Acute EC50 69600 μg/l Fresh water	Daphnia - Daphnia pulex - Neonate	48 hours
diphenyl ether	Acute LC50 35000 µg/l Fresh water Acute EC50 800 µg/l Marine water Acute LC50 670 µg/l Fresh water Acute LC50 1,7 mg/l Fresh water	Fish - Oncorhynchus mykiss Algae - Skeletonema costatum Daphnia - Daphnia magna Fish - Lepomis macrochirus	4 days 96 hours 48 hours 96 hours

Conclusion/Summary : Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

12.2 Persistence and degradability

Conclusion/Summary: Not available.

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Naphtha (petroleum), hydrodesulfurized heavy	-	10 to 2500	high
diphenyl ether	4,21	200	low

12.4 Mobility in soil

Date of issue/Date of revision: 25-7-2019Date of previous issue: 19-12-2018Version: 2.0110/14

HG furniture wax remover

SECTION 12: Ecological information

Soil/water partition coefficient (Koc)

: Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

PBT : Not applicable.

vPvB : Not applicable.

12.6 Other adverse effects: No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal

: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste

Packaging

Methods of disposal

- : The classification of the product may meet the criteria for a hazardous waste.
- : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Special precautions

: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number	UN1300	UN1300	UN1300	UN1300
14.2 UN proper shipping name	TURPENTINE SUBSTITUTE (Naphtha (petroleum), hydrodesulfurized heavy, mixture)	TURPENTINE SUBSTITUTE (Naphtha (petroleum), hydrodesulfurized heavy, mixture)	TURPENTINE SUBSTITUTE (Naphtha (petroleum), hydrodesulfurized heavy, mixture)	TURPENTINE SUBSTITUTE (Naphtha (petroleum), hydrodesulfurized heavy, mixture)
14.3 Transport hazard class(es)	3	3	3	3
14.4 Packing group	III	III	III	III

Date of issue/Date of revision : 25-7-2019 Date of previous issue : 19-12-2018 Version : 2.01 11/14

HG furniture wax remover

SECTION 14: Transport information

14.5 Environmental hazards	Yes.	Yes.	Yes.	Yes. The environmentally hazardous substance mark is not required.
Additional information	The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg. Hazard identification number 30 Limited quantity 5 L	The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.	The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg. Emergency schedules F-E, S-E	The environmentally hazardous substance mark may appear if required by other transportation regulations.

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code : Not applicable.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions : Not applicable.

on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Other EU regulations

Europe inventory : All components are listed or exempted.

Black List Chemicals

(76/464/EEC)

Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Seveso Directive

This product is controlled under the Seveso Directive.

Danger criteria

Category	

Con	tains	(Reg	ulation
(EC)	No 6	48/2	004)

aliphatic hydrocarbons	>30%
aromatic hydrocarbons	5-15%

Date of issue/Date of revision : 25-7-2019 Date of previous issue : 19-12-2018 Version : 2.01 12/14

SECTION 15: Regulatory information

perfumes: geraniol, limonene, citral

References

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol (Annexes A, B, C, E)

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

International lists

National inventory

Australia : All components are listed or exempted.
Canada : All components are listed or exempted.
China : All components are listed or exempted.

Turkey: Not determined.

United States : All components are listed or exempted.

Taiwan : Not determined.

Philippines : All components are listed or exempted.

New Zealand : All components are listed or exempted.

Malaysia : Not determined.

Republic of Korea : All components are listed or exempted.

Japan : Japan inventory (ENCS): Not determined.

Japan inventory (ISHL): Not determined.

15.2 Chemical safety

assessment

: This product contains substances for which Chemical Safety Assessments are still

required.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and

acronyms

: ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.

1272/2008]

DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Date of issue/Date of revision : 25-7-2019 Date of previous issue : 19-12-2018 Version : 2.01 13/14

HG furniture wax remover

SECTION 16: Other information

Classification	Justification
Flam. Liq. 3, H226	Expert judgment
STOT SE 3, H336	Expert judgment
STOT RE 1, H372 (central nervous system (CNS))	Expert judgment
Asp. Tox. 1, H304	Expert judgment
Aquatic Chronic 2, H411	Expert judgment

Full text of abbreviated H statements

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H372	Causes damage to organs through prolonged or repeated
	exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Full text of classifications [CLP/GHS]

Aquatic Acute 1, H400	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1, H410	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 2, H411	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Aquatic Chronic 3, H412	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Asp. Tox. 1, H304	ASPIRATION HAZARD - Category 1
EUH066	Repeated exposure may cause skin dryness or cracking.
Eye Irrit. 2, H319	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Flam. Liq. 3, H226	FLAMMABLE LIQUIDS - Category 3
Skin Irrit. 2, H315	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1, H317	SKIN SENSITISATION - Category 1
STOT RE 1, H372	SPECIFIC TARGET ORGAN TOXICITY - REPEATED
	EXPOSURE - Category 1
STOT SE 3, H336	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE
	(Narcotic effects) - Category 3

Date of printing : 25-7-2019

Date of issue/ Date of : 25-7-2019

revision

Date of previous issue : 19-12-2018

Version : 2.01

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Date of issue/Date of revision : 25-7-2019 Date of previous issue : 19-12-2018 Version : 2.01 14/14