# **Material Safety Data Sheet**



# HG quick and easy cooktop cleaner

## 1. Product and company identification

Product name	: HG quick and easy cooktop cleaner
	Pinnacle Home Solutions LLC 8711 E Pinnacle Peak Road Scottsdale AZ 85255 Email info@PinnacleHomeSolutions.com Tel 1.480.513.1317
Manufacturer	: HG International BV Damsluisweg 70 - NL-1332 EJ - Almere - The Netherlands +31 36 54 94 700
Code	: 109
	1
Validation date	: 15-1-2013.
Print date	: 15-1-2013.
In case of emergency	: +31 (0)36 54 94 777
Product type	: Liquid.

## 2. Hazards identification

Emergency overview		
Physical state	:	Liquid.
Color	:	Colorless.
Odor	:	Characteristic.
Signal word	1	WARNING!
Hazard statements	:	FLAMMABLE LIQUID AND VAPOR. COMBUSTIBLE. CAUSES EYE IRRITATION. MAY CAUSE SKIN IRRITATION. CONTAINS MATERIAL THAT MAY CAUSE TARGET ORGAN DAMAGE, BASED ON ANIMAL DATA. POSSIBLE CANCER HAZARD - CONTAINS MATERIAL WHICH MAY CAUSE CANCER, BASED ON ANIMAL DATA.
Precautionary measures	:	Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Do not breathe vapor or mist. Use only with adequate ventilation. Do not eat, drink or smoke when using this product. Avoid contact with eyes, skin and clothing. Keep away from heat, sparks and flame. Keep container tightly closed. Use personal protective equipment as required. Wash thoroughly after handling.
OSHA/HCS status	:	This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Potential acute health effects		
Inhalation	:	No known significant effects or critical hazards.
Ingestion	:	No known significant effects or critical hazards.
Skin	1	Slightly irritating to the skin.
Eyes	1	Severely irritating to eyes. Risk of serious damage to eyes.
Potential chronic health effect	<u>cts</u>	
Chronic effects	:	Contains material that may cause target organ damage, based on animal data.
Carcinogenicity	1	Contains material which may cause cancer, based on animal data. Risk of cancer depends on duration and level of exposure.
Mutagenicity	:	No known significant effects or critical hazards.
Teratogenicity	1	No known significant effects or critical hazards.

## 2. Hazards identification

Developmental effects	: No known significant effects or critical hazards.	
Fertility effects	: No known significant effects or critical hazards.	
Target organs	Contains material which may cause damage to the following organs: blood, kidneys, liver, spleen, upper respiratory tract, skin, central nervous system (CNS), eye, lens or cornea.	
Over-exposure signs/symp	<u>otoms</u>	
Inhalation	: No specific data.	
Ingestion	: No specific data.	
Skin	: Adverse symptoms may include the following: irritation redness	
Eyes	: Adverse symptoms may include the following: pain or irritation watering redness	
Medical conditions aggravated by over- exposure	: Pre-existing disorders involving any target organs mentioned in this MSDS as being at risk may be aggravated by over-exposure to this product.	
• • • • • • • •		

See toxicological information (Section 11)

## 3. Composition/information on ingredients

Name	CAS number	%
2-Propanol	67-63-0	5 - 10
glycine, n,n-bis(carboxymethyl)-, trisodium salt	5064-31-3	0.1 - 1

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

### 4. First aid measures

Eye contact	: Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately.
Skin contact	<ul> <li>In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention immediately.</li> </ul>
Inhalation	<ul> <li>Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention immediately.</li> </ul>
Ingestion	: Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.
Protection of first-aiders	<ul> <li>No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.</li> </ul>
Notes to physician	<ul> <li>No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.</li> </ul>

## 5. Fire-fighting measures

Flammability of the product	: Flammable liquid. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard.
Extinguishing media	
Suitable	: Use dry chemical, CO <sub>2</sub> , water spray (fog) or foam.
Not suitable	: Do not use water jet.
Special exposure hazards	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Hazardous thermal decomposition products	<ul> <li>Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides</li> </ul>
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

### 6. Accidental release measures

Personal precautions	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).
Environmental precautions	: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods for cleaning up	
Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## 7. Handling and storage

Handling
 Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use non-sparking tools. Take

### 7. Handling and storage

precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.

Storage : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

### 8. Exposure controls/personal protection

Ingredient	Exposure limits	
2-Propanol	ACGIH TLV (United States, 3/2012). TWA: 200 ppm 8 hours. STEL: 400 ppm 15 minutes. OSHA PEL 1989 (United States, 3/1989). TWA: 400 ppm 8 hours. TWA: 980 mg/m <sup>3</sup> 8 hours. STEL: 500 ppm 15 minutes. STEL: 1225 mg/m <sup>3</sup> 15 minutes. NIOSH REL (United States, 6/2009). TWA: 400 ppm 10 hours. TWA: 980 mg/m <sup>3</sup> 10 hours. STEL: 500 ppm 15 minutes. STEL: 500 ppm 15 minutes. STEL: 1225 mg/m <sup>3</sup> 15 minutes. STEL: 1225 mg/m <sup>3</sup> 15 minutes. TWA: 400 ppm 8 hours. TWA: 400 ppm 8 hours. TWA: 980 mg/m <sup>3</sup> 8 hours. TWA: 980 mg/m <sup>3</sup> 8 hours.	
Recommended monitoring procedures	<ul> <li>If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.</li> </ul>	
Engineering measures	Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.	
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.	
Personal protection Respiratory	: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.	

## 8. Exposure controls/personal protection

	• •
Hands	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Eyes	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
Skin	<ul> <li>Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> <li>When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.</li> </ul>
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## 9. Physical and chemical properties

Physical state	: Liquid.
Flash point	: Closed cup: 48°C (118,4°F) [Pensky-Martens.]
Color	: Colorless.
Odor	: Characteristic.
рН	: 10,3 to 10,8 [Conc. (% w/w): 100%]
Relative density	: 0,997
Volatility	: 9.5% (v/v), 7.48% (w/w)
Solubility	: Easily soluble in the following materials: cold water and hot water.

## 10. Stability and reactivity

Chemical stability	: The product is stable.
Conditions to avoid	: Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
Incompatible materials	<ul> <li>Reactive or incompatible with the following materials: oxidizing materials</li> </ul>
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.

## 11. Toxicological information

### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
2-Propanol	LD50 Dermal LD50 Oral	Rabbit Rat	12800 mg/kg 5000 mg/kg	-
glycine, n,n-bis (carboxymethyl)-, trisodium salt	LD50 Oral	Rat	1100 mg/kg	-

## 11. Toxicological information

Conclusion/Summary	: Not available.					
Chronic toxicity						
Conclusion/Summary	: Not available.					
Irritation/Corrosion						
Product/ingredient name	Result		Species	Score	Exposure	Observation
2-Propanol	Eyes - Moderate	e irritant	Rabbit	-	24 hours 100	-
	E Madanat		Datati		milligrams	
	Eyes - Moderate Eyes - Severe in		Rabbit Rabbit	-	10 milligrams	-
	Eyes - Severe II	mani	Rabbil	-	milligrams	-
	Skin - Mild irrita	nt	Rabbit	-	500	-
					milligrams	
Conclusion/Summary	: Not available.		•	!	•	
<u>Sensitizer</u>						
Conclusion/Summary	: Not available.					
Carcinogenicity						
Conclusion/Summary	: Not available.					
Classification						
Product/ingredient name	ACGIH	IARC	EPA	NIOSH	NTP	OSHA
2-Propanol	A4	3	-	-	-	-
glycine, n,n-bis	-	2B	-	-	-	-
(carboxymethyl)-, trisodium						
salt						
Mutagenicity						
Conclusion/Summary	: Not available.					
<u>Teratogenicity</u>						
Conclusion/Summary	: Not available.					
Reproductive toxicity						
Conclusion/Summary	: Not available.					
2. Ecological info	rmation					
cotoxicity	: Readily biodec	radable				
Aquatic ecotoxicity		,				

#### **Product/ingredient name** Result **Species Exposure** 2-Propanol Acute LC50 1400000 µg/l Marine water Crustaceans - Crangon crangon 48 hours Acute LC50 4200000 µg/l Fresh water Fish - Rasbora heteromorpha 96 hours glycine, n,n-bis Acute LC50 560000 to 1000000 µg/l Daphnia - Daphnia magna 48 hours (carboxymethyl)-, trisodium Fresh water salt Acute LC50 252000 µg/l Fresh water Fish - Lepomis macrochirus 96 hours **Conclusion/Summary** : Readily biodegradable Persistence/degradability : Readily biodegradable **Conclusion/Summary** Other adverse effects : No known significant effects or critical hazards.

### 13. Disposal considerations

Waste disposal

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

## 14. Transport information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
DOT Classification	UN1993	FLAMMABLE LIQUID, N.O.S. (2-Propanol)	3	111	PLANNASEE LIQUE	-
TDG Classification	UN1993	FLAMMABLE LIQUID, N.O.S. (2-Propanol)	3	111		-
Mexico Classification	UN1993	FLAMMABLE LIQUID, N.O.S. (2-Propanol)	3	111		-
ADR/RID Class	UN1993	FLAMMABLE LIQUID, N.O.S. (2-Propanol)	3	111		Special provisions 640 (E) Tunnel code (D/E)
IMDG Class	UN1993	FLAMMABLE LIQUID, N.O.S. (2-Propanol)	3			-
IATA-DGR Class	UN1993	FLAMMABLE LIQUID, N.O.S. (2-Propanol)	3	111		-

PG\* : Packing group

## 15. Regulatory information

· · · · · · · · · · · · · · · · · · ·	-	
HCS Classification	:	Combustible liquid Irritating material Carcinogen Target organ effects
U.S. Federal regulations	1	<b>TSCA 5(a)2 proposed significant new use rules</b> : 3(2H)-Isothiazolone, 5-chloro-2-methyl-; 3(2H)-Isothiazolone, 2-methyl-
		TSCA 8(a) IUR Exempt/Partial exemption: Not determined
		United States inventory (TSCA 8b): Not determined.
		<ul> <li>SARA 302/304/311/312 extremely hazardous substances: No products were found.</li> <li>SARA 302/304 emergency planning and notification: No products were found.</li> <li>SARA 302/304/311/312 hazardous chemicals: 2-Propanol</li> <li>SARA 311/312 MSDS distribution - chemical inventory - hazard identification:</li> <li>2-Propanol: Fire hazard, Immediate (acute) health hazard, Delayed (chronic) health hazard</li> </ul>
		Clean Water Act (CWA) 307: Benzene, methyl-
		Clean Water Act (CWA) 311: sodium hydroxide; Benzene, methyl-
Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs)	:	Not listed
Clean Air Act Section 602 Class I Substances	:	Not listed
Clean Air Act Section 602 Class II Substances	:	Not listed
DEA List I Chemicals (Precursor Chemicals)	:	Not listed
DEA List II Chemicals (Essential Chemicals)	:	Not listed

#### **SARA 313**

	Product name	CAS number	Concentration
Form R - Reporting requirements	2-Propanol	67-63-0	5 - 10
Supplier notification	2-Propanol	67-63-0	5 - 10

SARA 313 notifications must not be detached from the MSDS and any copying and redistribution of the MSDS shall include copying and redistribution of the notice attached to copies of the MSDS subsequently redistributed.

#### State regulations Massachusetts

: The following components are listed: ISOPROPYL ALCOHOL

- **New York**
- : None of the components are listed.
- New Jersey
- : The following components are listed: ISOPROPYL ALCOHOL; 2-PROPANOL
- Pennsylvania
- : The following components are listed: 2-PROPANOL

#### California Prop. 65

**WARNING:** This product contains less than 0.1% of a chemical known to the State of California to cause cancer. **WARNING:** This product contains less than 1% of a chemical known to the State of California to cause birth defects or other reproductive harm. HG quick and easy cooktop cleaner

## **15. Regulatory information**

Ingredient name	Cancer	Reproductive	No significant risk level	Maximum acceptable dosage level
4-allylanisole Benzene, methyl-	Yes. No.	No. Yes.	No. No.	No. 7000 μg/day (ingestion) 13000 μg/day (inhalation)

Canada inv	entory
<u>International</u>	regulations

: Not determined.

international regulations	
International lists	<ul> <li>Australia inventory (AICS): All components are listed or exempted.</li> <li>China inventory (IECSC): All components are listed or exempted.</li> <li>Japan inventory: Not determined.</li> <li>Korea inventory: Not determined.</li> <li>Malaysia Inventory (EHS Register): Not determined.</li> <li>New Zealand Inventory of Chemicals (NZIoC): Not determined.</li> <li>Philippines inventory (PICCS): All components are listed or exempted.</li> <li>Taiwan inventory (CSNN): Not determined.</li> </ul>
Chemical Weapons Convention List Schedule I Chemicals	: Not listed
Chemical Weapons Convention List Schedule II Chemicals	: Not listed
Chemical Weapons Convention List Schedule III Chemicals	: Not listed

## 16. Other information

Label requirements	: FLAMMABLE LIQUID AND VAPOR. COMBUSTIBLE. CAUSES EYE IRRITATION. MAY CAUSE SKIN IRRITATION. CONTAINS MATERIAL THAT MAY CAUSE TARGET ORGAN DAMAGE, BASED ON ANIMAL DATA. POSSIBLE CANCER HAZARD - CONTAINS MATERIAL WHICH MAY CAUSE CANCER, BASED ON ANIMAL DATA.		
Hazardous Material Information System (U.S.A.)	:		
	Health	2	
	Flammability	2	
	Physical hazards	0	
	Personal protection	В	

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on MSDSs under 29 CFR 1910. 1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

ŝ

National Fire Protection Association (U.S.A.) HG quick and easy cooktop cleaner

## 16. Other information



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

Date of printing	: 15-1-2013.
<b>C</b> ate of issue	<b>:</b> 15-1-2013.
Date of previous issue	: No previous validation.
Version	: 1
Prepared by	: Not available.

Indicates information that has changed from previously issued version.

#### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.